

Flexzilla Air Hose Assemblies

Flexzilla® Air Hoses offer superior flexibility for tight radius bends in both cold and warm environments. Engineered polymer-blend material permits use in environments where general purpose PVC and rubber hoses may become too stiff.



Extreme All-Weather Flexibility (-40° to 150°F / -40° to 65°C)

Features:-

1. No memory, lays flat
2. Kink resistant under pressure
3. Extreme all-weather flexibility, even in sub-zero temperatures!
4. Maximum working pressure: 300 PSI
5. 3:1 Safety factor
6. Excellent abrasion-resistant outer cover
7. Flexzilla® Hi-ViS colour makes hose more visible in the workplace

Part No	Hose Inside Diameter	Hose Outside Diameter	Hose Length	Male NPT fittings
HFZ3850YW2	3/8 in	0.61 in	50 ft	1/4 in
HFZ38100YW2	3/8 in	0.61 in	100 ft	1/4 in
HFZ1250YW3	1/2 in	0.74 in	50 ft	3/8 in
HFZ12100YW3	3/8 in	0.74 in	100 ft	3/8 in

Other sizes, lengths and connections available

Flexzilla Bulk Air Hose Program

The Flexzilla Bulk air hose program allows you to assemble customized hose lengths for specific applications. Available in 250ft drums.



available exclusively from



Cougarflex Hydraulics
59 Rixon Road
Finedon Road Industrial Estate
Wellingborough
Northamptonshire, NN8 4BA

tel: 01933 223354
fax: 01933 224522
flexzilla@cougarflex.co.uk



Bridge Engineering UK Limited
The Shires, Euro Business Park,
Rockingham Road,
Market Harborough,
Leicestershire, LE16 7QF

tel: 0845 4300401
fax: 0845 4300402
switchboard: 01536 355760
flexzilla@bridge-engineering.co.uk