

# Hi-ViS

## Flexzilla Pressure Washer Hose



Part No	Hose Inside Diameter	Hose Outside Diameter	Hose Length	Fitting Size	Temp. Range	Working Pressure
HFZ5222540YN	5/16 in	9/16 in	25 ft	M22 Connectors Female	-4 to 140°F	3600 PSI
HFZ5225040YW	5/16 in	9/16 in	50 ft	M22 Connectors Female	-4 to 140°F	3600 PSI
HFZ332540YW	3/8 in	11/16 in	25 ft	3/8 in Male Rigid x 3/8 in Female Swivel	-4 to 140°F	4000 PSI
HFZ335040YW	3/8 in	11/16 in	50 ft	3/8 in Male Rigid x 3/8 in Female Swivel	-4 to 140°F	4000 PSI

Other sizes, lengths and connections available



### Flexzilla® Pressure Washer Hose Features:

- Designed for professional-duty cold water pressure washers
- Dual overbraid technology
- Polyester braid over inner tube
- Brass-coated steel braid over the polyester
- Clear polyurethane “non-marking” outer jacket
- 4:1 safety factor
- Rated up to 140°F / 65°C maximum
- Extremely tough, and easy to handle
- For cold water use only
- Flexzilla® Hi-ViS colour makes hose more visible in the workplace

available exclusively from



Cougarflex Hydraulics  
59 Rixon Road  
Finedon Road Industrial Estate  
Wellingborough  
Northamptonshire, NN8 4BA

tel: 01933 223354  
fax: 01933 224522  
[flexzilla@cougarflex.co.uk](mailto:flexzilla@cougarflex.co.uk)



Bridge Engineering UK Limited  
The Shires, Euro Business Park,  
Rockingham Road,  
Market Harborough,  
Leicestershire, LE16 7QF

tel: 0845 4300401  
fax: 0845 4300402  
switchboard: 01536 355760  
[flexzilla@bridge-engineering.co.uk](mailto:flexzilla@bridge-engineering.co.uk)